



ARKOS FLUSHING OIL Flushing Oil

ARKOS FLUSHING OIL is formulated for flushing of engine, transmission and other lubrication systems after the old oil has been drained out. It is a blend from a superior highly refined light mineral oil. This oil does not contain any detergents and thus can be used for flushing of systems where NIL contaminations from calcium, or soap containing, materials are required.

Benefits

- **ARKOS FLUSHING OIL** is hydrocarbon based and is severely hydro-processed. It is fully compatible with industrial materials.
- The ISO VG 32 viscosity grade helps the oil to penetrate the remote locations of any system where flushing is required.
- Its high flash point makes the product suitable for flushing Heat Transfer systems as well.

Applications

ARKOS FLUSHING OIL is used for flushing of engines and transmission systems

Performance Specifications

ARKOS FLUSHING OIL meet the requirements of JIS K 2213 Type 1 (without additive) and MHI Power Type 1 flushing oil.

Characteristics (Typical Values)

ARKOS FLUSHING OIL		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Viscosity at 100°C	mm ² /s	5.39
Viscosity at 40°C	mm ² /s	31.5
Flash Point COC	°C	214
Pour Point	°C	-12
Total Acid Number	mgKOH/g	0.03
Sulphur	mg/kg	< 10
Density at 29.5°C	'gm/cc	0.863

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle/machine/equipment.



Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: