

## **POWEROIL CRUISE SONIC XP 0W-20**

### **Passenger Car Engine Oil**

**POWEROIL CRUISE SONIC XP 0W-20** is a fully synthetic, high- performance engine oil, formulated with Synthetic base oils and high performance additive packages. The engine oil is specifically formulated to meet the requirements of engines fitted on all new generation passenger cars to ensure superlative performance.

### **Benefits**

- Special synthetic base stocks and additives ensure that Cruise CRUISE SONIC XP, SAE 0W-20 maintains ideal viscosity under a wide range of conditions, thereby reducing friction, fuel consumption and therefore noxious emissions. The engine oil formulated with Synthetic Technology base oils, decrease volatility which diminish oil consumption thus reducing emissions from unburned oil in exhaust.
- The Synthetic Base oil components increase adhesion of a film of oil to metal parts even when the engine has been standing for long periods, ensuring easy starting and greatly reducing wear in the critical first phases of ignition.
- CRUISE SONIC XP maintain its viscosity and lubricity even under gruelling driving conditions, minimizing engine wear, ensuring long life for all moving parts and substantially reduces the need for engine servicing and overhauling.
- This oil delivers increased detergency, keeping engines free of sludge, varnish, and other harmful substances.
- Offers excellent thermal & oxidation resistance. In addition, provides excellent wear protection.
- Excellent protection against Low Speed Pre-ignition (LSPI) issues.

### **Applications**

POWEROIL CRUISE SONIC XP 0W-20 is suitable for all new generation passenger cars.

### **Performance Specifications**

**POWEROIL CRUISE SONIC XP 0W-20** meets the requirements of the following service specifications:

- API SP
- ILSAC GF-6

## Characteristics (Typical Values)

<b>POWEROIL CRUISE SONIC XP 0W-20</b>		
<b>TEST PARAMETERS</b>	<b>METHOD</b>	<b>TYPICAL VALUES</b>
Density at 29.5°C	am/cc	0.837
Viscosity at 100 °C	mm <sup>2</sup> /s	8.18
Viscosity at 40 °C	mm <sup>2</sup> /s	42.62
Viscosity at -35 °C	mPa·s	5952
Viscosity Index	-	175
Flash Point	°C	208
Pour Point	°C	-35

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle.