

POWEROIL GEAR EP 140 Gear Oil

POWEROIL GEAR EP 140 oils are extreme pressure multipurpose gear oils formulated from solvent refined high viscosity index base stocks and selected additives.

Benefits

- BIS: 1118 – 1992 EP type
- API Service Classification GL-4 level
- U.S. Military MIL-L-2105
- UK Defense CS 3000A Specifications

Applications

Recommended for use in gearboxes and rear axles where extreme pressure properties are required particularly for hypoid and bevel gears.

Not recommended for industrial gears having copper or copper alloy parts.

Performance Specifications

POWEROIL GEAR EP 140 meets the requirements of the following specifications:

- API GL-4

Typical Characteristics

POWEROIL GEAR EP 140		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Kin. Viscosity @100°C	ASTM D 445	16-18
Viscosity Index	ASTM D 2270	90
Flash Point	ASTM D 92	180
Pour Point	ASTM D 97	-9
Channel Point	-	-18

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle.



Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: www.apar.com