



FOR THE **ROAD** AHEAD



ARKOS DRIVZ 20000 5W-40

Passenger Car Engine Oil

ARKOS DRIVZ 20000 5W-40 is a high-performance engine oil, formulated with synthetic technology base oils and high-performance additive packages. The engine oil is specifically formulated to meet the requirements of gasoline Engines of passenger cars.

Benefits

- Special synthetic technology base stocks and additives ensure that ARKOS DRIVZ 20000, SAE 5W-40 maintains ideal viscosity under a wide range of conditions, thereby reducing friction, fuel consumption and therefore noxious emissions. The engine oil formulated with synthetic technology base oils, decrease volatility which diminish oil consumption thus reducing emissions from unburned oil in exhaust.
- The superior base oil components increase adhesion of a film of oil to metal parts even when the engine has been standing for long periods, ensuring easy starting and greatly reducing wear in the critical first phases of ignition.
- ARKOS DRIVZ 20000 maintains its viscosity and lubricity even under grueling driving conditions, minimizing engine wear, ensuring long life for all moving parts and substantially reduces the need for engine servicing and overhauling.
- This oil delivers increased detergency, keeping engines free of sludge, varnish and other harmful substances.
- Offers excellent oxidation resistance. In addition, provides excellent wear protection.

Applications

Recommended for lubrication of gasoline engines of passenger cars.

Performance Specifications

ARKOS DRIVZ 20000 5W-40 is API licensed for API SN Specification

ARKOS DRIVZ 20000 5W-40 also meets the below requirements specification



FOR THE ROAD AHEAD



- ACEA A3/B3/B4-08
- MB 229.3
- RENAULT RN 0700, 0710
- PORSCHE A40
- VW 502 00 + 505 00

Characteristics (Typical Values)

| ARKOS DRIVZ 20000 5W-40 | | |
|-------------------------|--------------------|----------------|
| TEST PARAMETERS | METHOD | TYPICAL VALUES |
| Viscosity at 100 °C | mm ² /s | 14.2 |
| Viscosity at 40 °C | mm ² /s | 86 |
| Viscosity at -20 °C | mPa·s | 6275 |
| Viscosity Index | - | 172 |
| Flash Point | °C | 210 |
| Pour Point | °C | -33 |
| Density at 29.5°C | gm/cc | 0.841 |

Note: Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle/machine/equipment.



Disclaimer: APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: www.apar.com