



FOR THE **ROAD** AHEAD



## ARKOS SLIK EP2

### Grease

ARKOS SLIK EP2 is a high performance, heavy duty extreme pressure grease made from Lithium soap to withstand high pressure and harsh operating condition. This is a generalpurpose grease for industrial applications requiring a NLGI 2 grade extreme pressure grease and high operating temperature.

### Benefits

- Load Carrying Capacity Boosters provide superior film strength for better load carrying capability.
- Good retention of structure under extreme operating conditions.
- Very good protection against rust and corrosion.
- Very good pumping ability.

### Applications

ARKOS SLIK EP 2 is recommended for use in lubrication of slide, ball and roller bearing, wheel -bearings, universal joints, chassis and various shock loaded or vibrating application in transport, agriculture and off-road vehicles.

### Performance Specifications

ARKOS SLIK EP2 meets the following performance requirements:

- NLGI 2

### Characteristics (Typical Values)

ARKOS SLIK MP		
TEST PARAMETERS	METHOD	TYPICAL VALUES
Thickener Type/Soap	-	Lithium
Structure	Visual	Smooth Homogeneous/Yellow
Thermal Usage Range	°C	-20 to 160
Penetration	@25°C, 60 stokes	265 – 295
Drop point, °C	ASTM D 566	190 Min.



# FOR THE ROAD AHEAD



Four Ball Machine Welding Test, Kg	ASTM D 2596	250
Worked Penetration, 60x	ASTM D 217	220-250
Timken Test , Kg	ASTM D 2509	40

**Note:** Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your vehicle/machine/equipment.



**Disclaimer:** APAR makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility. Website: [www.apar.com](http://www.apar.com)