

# POWER ATF D II D

## Automatic Transmission Fluid

POWER AUTOMATIC TRANSMISSION FLUID D II is a high-performance automatic transmission fluid designed to provide smooth and efficient operation in all modern automatic transmission and power steering.

### Advantages

- Ensures efficient operation of power steering units under all conditions.
- High thermal stability protects against deposits and oil thickening prolonging the life of components and lubricants.
- Enhanced friction characteristics and wear protection maintain effective operation of equipment.
- Effective seal compatibility reduces the risk of leakages.

### Typical Characteristics

Characteristics	Unit	Test Method	Specifications
Density @29.5°C.	gm/cc	ASTM D 1298	0.84
Kin. Viscosity @40°C	cst	ASTM D 445	37.3
Kin. Viscosity @100°C	cst	ASTM D 445	7.2
Viscosity Index	-	ASTM D 2270	160
Flash Point	°C	ASTM D 92	180
Pour Point	°C	ASTM D 97	-40

**Note:** Always consult your owner's manual to check for recommended viscosity grade and specifications of oil for your particular vehicle.

### Health, Safety & Environment

POWER ATF D II D is not expected to produce any significant health & safety hazard when used properly in intended application. However, avoid skin contacts by using proper Gloves. After skin contact, wash immediately with soap and water. For details, follow Material Safety Data Sheet.

Disposing of any used oil in drainage is hazardous to environment. Take used oil to an authorized Collection point.